

HYPER SERIES HAMMERS

HYPER 41

Hammer 105 mm (4 1/8") - 127 mm (5") diameter holes

Highly dependable hammer with simple but rugged design

- Optimum performance at air pressures ranging from 10 to 24 bar (150-350 psi)
- Standard 2 3/8" API reg. pin backhead
- DHD340 / COP44 bit shank fitting

Component parts

Ref	Description	Part number
1	Backhead	HSH413801M
2	Backhead O-ring	IPBOR02
3	Check valve	IPRCV02
4	Check valve spring	IPRCVS02
5	Compression ring	HSH4128
6	Diverter	HSH4120
7	Piston DHD340	HSH4103
8	Wear Sleeve	HSH4100
9	Piston retaining ring	HSH4132
10	Bit retaining O-ring	IPBROR01
11	Bit retainer DHD340	HSH4137091
12	Breakout washer	HSH4126
13	Chuck DHD340	HSH4135091
	Service Kit Hyper 41 incl. (2,4,5,10,12)	HSH41SERVKIT
	Repair Kit Hyper 41 incl. (2,3,4,5,9,10,11,12,13)	HSH41REPKIT
	Complete Hammer	BR41H04

Air consumption

PSI	BAR	m ³ /min	ft ³ /min
100	6.9	3.4	118.7
150	10.3	6.3	222.5
200	13.8	9.4	330.6
250	17.2	13.2	466.2
300	20.7	16.3	576.3
350	24.2	20.4	720.4

Hammer specification

	Imperial	Metric
Weight (less bit)	77 lbs	35 kg
Length (less bit)	37.1"	942 mm
Outside dia.	3.75"	95 mm
Piston weight	17.6 lbs	8 kg

